

## DB 200 Sound level meter

Integrating-averaging with storage function



### FIVE DIFFERENT MEASUREMENT MODES

- **Mode 1** : Conventional sound level meter
- **Mode 2** : Conventional sound level meter with storage.
- **Mode 3** : Conventional and integrating-averaging sound level meter
- **Mode 4** : Integrating-averaging sound level meter with storage.
- **Mode 5** : Sound level meter "calculator" of two sound sources.

### MEASURED VALUES

- Weighted sound level : **L**
- Equivalent continuous level : **Leq**
- Sound exposure level : **LE**
- Peak pressure level : **Lpk**

### RESULTS & ADDITIONAL INFORMATION

- Maximum and minimum values, peak values
- **L01-L10-L50-L90** statistics distribution of measured values.
- Presence and percentage of overload input stages, measurement time.
- Residual autonomy of batteries or battery, measuring capacity remaining.

### DATA DISPLAY

The DB200 sound level meter is supplied with LDB200 software for display data and measurement report printing.



### I/O INTERFACE

Launching and stopping of the measurement by external control.  
Detection of sensitive levels for alarms activation  
Analogue output 0-10V DC.

### STANDARDS

As per following standards :  
**Sound level meter** : NF EN 61672-1 (2003)- NF EN 60651 (1994) – NF EN 60804 (2000).  
**CE conformity** : EN 61010 – EN 61000 generic and as per product standards.

## TECHNICAL FEATURES

### Metrology

Accuracy.....	Class 2	Logging time for short Leq (DI).....	from 1 s to 60 s
Microphone type.....	Electret ICP – ½" - Sensibility : 15 mV/Pa	Sampling for Lp.....	from 1 s to 60 s
Measuring type.....	Free-field	Measured values.....	LXY – LXYmax – LXYmin - LXeq,T – LXeq,DI – LXE – LXeq,DImax – LXeq,DImin
Measurement dynamic.....	Lp/Leq : 100 dB - Lpk : 50 dB	Statistics indices LXN on Lp and Leq samples.....	LX01 – LX10 – LX50 – LX90 – LX95 – resolution 1dB.
A-weighted measurement range.....	30-130 dB	Measured values simultaneously -	
C-weighted measurement range.....	35-130 dB	Storage mode.....	All according LXY or LXeq choice
Z-weighted measurement range.....	35-130 dB	Detection and	
Peak channel measurement range.....	83-133 dB	percentage of overload.....	Alarm graphics and calculation of percentage during the storage
X frequency weighting.....	A – C – Z		
Y frequency weighting.....	F (fast) – S (slow) I (impulse) – Peak (pk)		

### SOUND LEVEL METER

Screen.....	graphic display 240 x 160 pixels – LCD monochrome 16 levels – digital and analogue display – 3D effect on display
Keypad.....	8 sensitive keys
Internal clock.....	permanent, saved by internal battery
Memory module.....	integrated Micro SD card type – data transfer by USB cable
Environment.....	from -10 °C to +50 °C
Humidity.....	from 0 to 90% HR
Dimensions (L x l x e).....	270 x 70 x 40 mm
Weight (including batteries).....	280 gr
Fixing.....	Insert at rear for fixing on tripod

### OPERATING

5 measurement modes.....	conventional – conventional with storage – conventional and integrating – integrating with storage – calculator S1 + S2
Storage and measurement capacity.....	L-Leq mode : 24h L-St or Leq-St mode : according sampling or elementary logging time Memory capacity : 25 periods of 86 500 values – ex : 24 hours / Leq 1s
I/O Interface : .....	Output 0-10V DC : 0-130dB Start/Stop measurement order : TTL level maximal 5V Output for alarm activation : TTL level 3.3 V
Measurement launching.....	By keyboard or I/O controlled
Power – Autonomy.....	Batteries : 3 x LR6/AA – minimum autonomy : 15 hours at 20 °C Optional rechargeable Li-Ion battery : minimum autonomy : more than 24 h at 20 °C Electrical power adapter 5V, USB format.
Guarantee.....	2 years

### SUPPLIED WITH

- Windshield
- Transport case
- 3 LR6-AA batteries
- Calibration certificate
- Transfer cable USB type
- LDB200 software

### ACCESSORIES

- Tripod
- Acoustic calibrator class 2
- Rechargeable Li-Ion battery
- Charger – electrical power adapter USB type
- Jack cables for I/O interface



Acoustic  
calibrator

[www.kimo.fr](http://www.kimo.fr)



EXPORT DEPARTMENT  
Tel : + 33. 1. 60. 06. 69. 25 - Fax : + 33. 1. 60. 06. 69. 29  
e-mail : [export@kimo.fr](mailto:export@kimo.fr)

Distributed by :

**زیست تجهیز پویش**  
(سهامی فاخر)

آدرس: تهران، خ مطهری، خ فجر، ک افشار، پ ۱۶، ط ۱  
تلفن: ۸۸۸۲۷۷۳۳ - ۸۸۸۲۶۸۷۵ - فکس: ۸۸۸۲۶۷۹۱  
پست الکترونیکی: [info@PooyeshEnviro.ir](mailto:info@PooyeshEnviro.ir)